CV300 SERIES™ | CUT VINYL



Polymeric cut vinyls with a high tack permanent adhesive and air-egress liner. Thanks to the unique combination of the high tack adhesive with air-egress liner, CV300 SeriesTM ensures easy, dry application on a wide variety of substrates.

CV300 Series™

Soft in nature, CV300 Series™ calendered opaque vinyls are films with excellent dimensional stability, suitable for flat, slightly curved and mildly textured surfaces

Effortless cutting and weeding

Easy to dry-apply

Adheres to difficult surfaces*

High opacity

Rolls of 1220mm x 45,7m

Outdoor durability up to 5 years for Black/ White and up to 4 years for other colours**

For ease of installation, apply CV300 Series™ cut vinyl with RTape Conform® 4761RLA application tape for air-egress liners

Applications

Indoor lettering

Wall decorations & decals

Window signage

Event signage

P.O.P. signage

In-Store promotions



^{*} On hard-to-adhere surfaces, we recommend a test to confirm that the vinyl will bond before full application.

^{**} Vertical exposure, Mid-EU climate

CV300 SERIES CUT VINYL

PRODUCT OVERVIEW ▶

GLOSS



















MATT

ORANGE






















Colour	SKU#	Size
Gloss		
Black	EC3745-48150	1220mm x 45,7m
White	EC3281-48150	1220mm x 45,7m
Blue	EC7112-48150	1220mm x 45,7m
Hunter Green	EC8778-48150	1220mm x 45,7m
Cardinal Red	EC2472-48150	1220mm x 45,7m
Orange	EC5555-48150	1220mm x 45,7m
Dark Grey	EC1270-48150	1220mm x 45,7m
Sunflower Yellow	EC4267-48150	1220mm x 45,7m
Bright Yellow	EC3048-48150	1220mm x 45.7m

Colour	SKU#	Size
Matt		
Black	EC9284-48150	1220mm x 45,7m
White	EC1955-48150	1220mm x 45,7m
Medium Blue	EC7288-48150	1220mm x 45,7m
Hunter Green	EC4325-48150	1220mm x 45,7m
Cardinal Red	EC9882-48150	1220mm x 45,7m
Orange	EC7422-48150	1220mm x 45,7m
Dark Grey	EC9012-48150	1220mm x 45,7m
Sunflower Yellow	EC1986-48150	1220mm x 45,7m
Silver	EC1982-48150	1220mm x 45,7m
Gold	EC3477-48150	1220mm x 45,7m

CV300 SERIES CUT VINYL







CV300 Series™ is a high-end multipurpose cut vinyl suitable for letterings and decals on walls, windows and other storefronts.

TECHNICAL DATA ▶

Physical Properties						
Film	Film Adhesive Liner Opacity		Polymeric calendared vinyl			
Adh			High tack permanent acrylic			
Line			165gsm kraft air Egress			
Opa			92% min			
This		Film	75 micron			
Thickness	Kness	Film + adhesive	100 micron			
A -JL		Stainless steel - 20min	20 N/25mm			
Adhesion	esion	Stainless steel - 24hrs	24 N/25mm			
Wate	Wataba	Film + Adhesive	125-130 gsm			
Weight	gnt	Total w/Liner	280-290 gsm			
Conditions for use						

Conditions for us Shelf Life*

Outdoor Durability**

Up to 5 years for Black/White Up to 4 years for other colours

Min Application Temp

-24°C to +60°C Service Temp

Solvent Resistance*** Good for most petroleum-based solvents and lower alipathic alcohols. For ultimate solvent resistance, edge sealing is recommended.

Water Resistance Excellent

> * Stored at 22°C /50-55%RH **Vertical exposure, Mid-EU climate *** For ultimate solvent resistance, edge sealing is recommended.

