EZ-COLOR CUT VINYL



Polymeric cut vinyls with a high tack permanent adhesive and air-egress liner. Thanks to the unique combination of the high tack adhesive with air-egress liner, EZ-ColorTM ensures easy, dry application on a wide variety of substrates.

EZ-Color™

Soft in nature, EZ-Color™ calendared opaque vinyls are films with excellent dimensional stability, suitable for flat, slightly curved and mildly textured surfaces

Effortless cutting and weeding

Easy to dry-apply

Adheres to difficult surfaces*

High opacity.

Rolls of 1220mm x 45,7m

Outdoor durability up to 6 years

For ease of installation, apply EZ-Color™ cut vinyl with RTape Conform® 4761RLA application tape for air-egress liners

Applications

Indoor and outdoor lettering

Industrial markings

Fleet markings

Wall decorations & decals

Window signage

Event signage

P.O.P. signage

In-Store promotions

Safety signage



^{*} On hard-to-adhere surfaces, we recommend a test to confirm that the vinyl will bond before full application.




PRODUCT OVERVIEW ▶

GLOSS





















MATT





















Colour	SKU#	Size
Gloss		
Black	EC3745-48150	1220mm x 45,7m
White	EC3281-48150	1220mm x 45,7m
Blue	EC7112-48150	1220mm x 45,7m
Medium Green	EC2235-48150	1220mm x 45,7m
Cardinal Red	EC2472-48150	1220mm x 45,7m
Orange	EC5555-48150	1220mm x 45,7m
Medium Grey	EC9944-48150	1220mm x 45,7m
Dark Grey	EC1270-48150	1220mm x 45,7m
Sunflower Yellow	EC4267-48150	1220mm x 45,7m
Bright Yellow	EC3048-48150	1220mm x 45,7m

Colour	SKU#	Size
Matt		
Black	EC9284-48150	1220mm x 45,7m
White	EC1955-48150	1220mm x 45,7m
Medium Blue	EC7288-48150	1220mm x 45,7m
Medium Green	EC1295-48150	1220mm x 45,7m
Cardinal Red	EC9882-48150	1220mm x 45,7m
Orange	EC7422-48150	1220mm x 45,7m
Medium Grey	EC1024-48150	1220mm x 45,7m
Silver	EC1982-48150	1220mm x 45,7m
Sunflower Yellow	EC1986-48150	1220mm x 45,7m
Gold	EC3477-48150	1220mm x 45,7m









EZ-Color is a high-end multipurpose cut vinyl, not only suitable for standard markings on windows and vehicles, but also for interior wall decoration and industrial signage.

TECHNICAL DATA ▶

Physical Properties						
	Film Adhesive		Polymeric calendared vinyl			
			High tack permanent acrylic			
Liner			165gsm kraft air Egress			
_	Opacity		92% min			
	Thickness	Film	75 micron			
		Film + adhesive	100 micron			
	Adhesion	Stainless steel - 20min	20 N/25mm			
		Stainless steel - 24hrs	24 N/25mm			
	Mairch.	Film + Adhesive	125-130 gsm			
	weignt	Total w/Liner	280-290 gsm			
Conditions for use						

Conditions for use
Shelf Life* 1 year

Outdoor Durability** Up to 6 years

Min Application Temp +2°C

Service Temp -24°C to +60°C

Solvent Resistance*** Good for most petroleum-based solvents and lower alipathic alcohols. For ultimate solvent resistance, edge sealing is recommended.

Water Resistance Excellent

* Stored at 22°C /50-55%RH

**Mid continental U.S. vertical

*** For ultimate solvent resistance, edge sealing is recommended.

