



# 30.900N | Total Mirror

This polyester printable mirror film is suitable for indoor and short-term outdoor use. With its two-way mirror effect, it seamlessly adapts to flat and subtly curved surfaces, providing design flexibility. This film is ideal for decorative applications in diverse settings like fashion stores, hospitals, and petrol stations.

### FACE FILM

PET, silver mirror

Thickness (µm)	190
----------------	-----

### ADHESIVE

Clear solvent-based acrylic, permanent

Thickness (µm)	20
Adhesion to steel	FINAT FTM 1
20 minutes (180°) N/25mm	11
24 hours (180°) N/25mm	13

### RELEASE LINER

Clear PET liner

Thickness (µm)	20
----------------	----

### PROTECTION FILM

Thickness (µm)	20
----------------	----

### PRODUCT APPLICATION

sssssss	
Application temperature (°C)	10 to 25
Service temperature (°C)	-30 to 60

### DURABILITY

Outdoor durability (years)	1	Vertical exposure, Mid-EU climate
Shelf life (months)	18	

### ROLL SIZES

1220mm x 25m  
1220mm x 50m

### PRINTING METHOD

UV      Angular alignment of printheads only

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

