

# TITAN APEX GREEN | TAGX-170

Durable high tack fluorescent green print vinyl with micro channel liner for air egress application. The cast PVC construction provides excellent opacity and colour intensity.

## FACE FILM

Cast PVC, fluorescent green

Thickness (µm)	170
----------------	-----

## ADHESIVE

Clear solvent-based acrylic, high tack permanent

Thickness (µm)	40
Adhesion to steel	FINAT FTM 1
20 minutes (180°) N/25mm	30
24 hours (180°) N/25mm	37

## RELEASE LINER

Structured lay-flat kraft paper liner, double-sided PE-coated

Weight (gsm)	160
--------------	-----

## PRODUCT APPLICATION

Application method	Dry
Application temperature (°C)	10 to 30
Service temperature (°C)	-5 to 50

## DURABILITY

Shelf life (months)	12
Outdoor durability (months)	12* Northern-EU climate, vertical exposure

\*Lamination is recommended and can extend the outdoor durability of the film

## ROLL SIZES

1370mm x 25m  
1370mm x 50m

## PRINTING METHOD

(Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in TITAN material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

## TITAN APEX PINK | TAPX-170

Durable high tack fluorescent pink print vinyl with micro channel liner for air egress application. The cast PVC construction provides excellent opacity and colour intensity.

### FACE FILM

Cast PVC, fluorescent pink

Thickness (µm)	170
----------------	-----

### ADHESIVE

Clear solvent-based acrylic, high tack permanent

Thickness (µm)	40
Adhesion to steel	FINAT FTM 1
20 minutes (180°) N/25mm	30
24 hours (180°) N/25mm	37

### RELEASE LINER

Structured lay-flat kraft paper liner, double-sided PE-coated

Weight (gsm)	160
--------------	-----

### PRODUCT APPLICATION

Application method	Dry
Application temperature (°C)	10 to 30
Service temperature (°C)	-5 to 50

### DURABILITY

Shelf life (months)	12	
Outdoor durability (months)	6*	Northern-EU climate, vertical exposure

\*Lamination is recommended and can extend the outdoor durability of the film

### ROLL SIZES

1370mm x 25m  
1370mm x 50m

### PRINTING METHOD

(Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in TITAN material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

## TITAN APEX RED | TARX-170

Durable high tack fluorescent red print vinyl with micro channel liner for air egress application. The cast PVC construction provides excellent opacity and colour intensity.

### FACE FILM

Cast PVC, fluorescent red

Thickness (µm)	170
----------------	-----

### ADHESIVE

Clear solvent-based acrylic, high tack permanent

Thickness (µm)	40
Adhesion to steel	FINAT FTM 1
20 minutes (180°) N/25mm	30
24 hours (180°) N/25mm	37

### RELEASE LINER

Structured lay-flat kraft paper liner, double-sided PE-coated

Weight (gsm)	160
--------------	-----

### PRODUCT APPLICATION

Application method	Dry
Application temperature (°C)	10 to 30
Service temperature (°C)	-5 to 50

### DURABILITY

Shelf life (months)	12	
Outdoor durability (months)	6*	Northern-EU climate, vertical exposure

\*Lamination is recommended and can extend the outdoor durability of the film

### ROLL SIZES

1370mm x 25m  
1370mm x 50m

### PRINTING METHOD

(Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in TITAN material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

## TITAN APEX YELLOW | TAYX-170

Durable high tack fluorescent yellow print vinyl with micro channel liner for air egress application. The cast PVC construction provides excellent opacity and colour intensity.

### FACE FILM

Cast PVC, fluorescent yellow

Thickness (µm)	170
----------------	-----

### ADHESIVE

Clear solvent-based acrylic, high tack permanent

Thickness (µm)	40
Adhesion to steel	FINAT FTM 1
20 minutes (180°) N/25mm	30
24 hours (180°) N/25mm	37

### RELEASE LINER

Structured lay-flat kraft paper liner, double-sided PE-coated

Weight (gsm)	160
--------------	-----

### PRODUCT APPLICATION

Application method	Dry
Application temperature (°C)	10 to 30
Service temperature (°C)	-5 to 50

### DURABILITY

Shelf life (months)	12	
Outdoor durability (months)	12*	Northern-EU climate, vertical exposure

\*Lamination is recommended and can extend the outdoor durability of the film

### ROLL SIZES

1370mm x 25m  
1370mm x 50m

### PRINTING METHOD

(Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in TITAN material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.